



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 **RS3000**

Features

- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- Low Forward Voltage Drop
- **High Current Capability**
- High Voltage
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

-					
	MCC	Device	Maximum	Maximum	Maximum
	Part	Marking	Recurrent	RMS	DC
	Number		Peak Reverse	Voltage	Blocking
			Voltage		Voltage
	RS3000	RS3000	3000V	2100V	3000V

Electrical Characteristics @ 25°C Unless Otherwise Specified


iooti ioai onalaotoliotico 🍥 20 o onicos otiloi nico opecinic					
Average Forward Current	I _{F(AV)}	200mA	T _A = 50°C		
Peak Forward Surge Current	I _{FSM}	30A	8.3ms, half sine		
Maximum Instantaneous Forward Voltage					
	V_{F}	4.0V	I _{FM} = 0.5A; T _A = 50°C		
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μA 50μA	T _A = 25°C T _A = 100°C		
Typical Junction Capacitance	CJ	30pF	Measured at 1.0MHz, V _R =4.0V		

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

200 Milliamp **High Voltage** 3000 Volts

Silicon Rectifier


DO-41




DIMENSIONS									
	INCHES		MM						
DIM	MIN	MAX	MIN	MAX	NOTE				
Α	.166	.205	4.10	5.20					
В	.080	.107	2.00	2.70					
С	.028	.034	.70	.90					
D	1.000		25.40						




Micro Commercial Components



Instantaneous Reverse Current - Micro Amps*versus* Percent Of Rated Peak Reverse Voltage - Volts



Average Forward Rectified Current - Amperes/ersus Ambient Temperature -°C



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles



Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 50Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.