

ROHS

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 ER300 THRU ER306

Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Superfast recovery times-epitaxial construction
- Low leakage, High surge capability
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings

- Operating Junction Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

Typical Thermal Resistance 20°C/W Junction to ambient

MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage	_	Voltage
ER300	ER300	50V	35V	50V
ER301	ER301	100V	70V	100V
ER301A	ER301A	150V	105V	150V
ER302	ER302	200V	140V	200V
ER303	ER303	300V	210V	300V
ER304	ER304	400V	280V	400V
ER306	ER306	600V	420V	600V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	3 A	T _A = 55°C
Peak Forward Surge Current	I _{FSM}	125A	8.3ms, half sine
Maximum			
Instantaneous			
Forward Voltage			
ER300-302	V_F	0.95V	$I_{FM} = 3.0A;$
ER303-304		1.25V	$T_A = 25^{\circ}C$
ER306		1.70V	
Maximum DC			
Reverse Current At	I_{R}	5μΑ	$T_A = 25^{\circ}C$
Rated DC Blocking		300μΑ	T _A = 125°C
Voltage		•	
Maximum Reverse			
Recovery Time			
	T_{rr}	35ns	$I_F=0.5A, I_R=1.0A,$
			I _{rr} =0.25A
Typical Junction			
Capacitance			
	C_{J}	35pF	Measured at
			1.0MHz, $V_R=4.0V$

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

3 Amp Super Fast Recovery Rectifier 50 to 600 Volts

DO-201AD




DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.287	.374	7.30	9.50		
В	.189	.208	4.80	5.30		
С	.048	.052	1.20	1.30		
D	1.000		25.40			

ER300 thru ER306

RATING AND CHARACTERISTIC CURVES




Micro Commercial Components



AMBIENT TEMPERATURE, °C

Fig. 1-REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM

Fig. 2-MAXIMUM AVERAGE FORWARD CURRENT RATING







Fig. 3-TYPICAL REVERSE CHARACTERISTICS

Fig. 4-FORWARD CURRENT DERATING CURVE






Fig. 5-MAXIMUM NON-REPETITIVE SURGE CURRENT

Fig. 6-TYPICAL JUNCTION CAPACITANCE



Micro Commercial Components

Ordering Information:

Device	Packing	
(Part Number)-TP	Tape&Reel 1.2Kpcs/Reel	
(Part Number)-AP	Ammo Packing;1.2Kpcs/AmmoBox	
(Part Number)-BP	Bulk;12Kpcs/Carton	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Revision: B 3 of 3 2013/01/01