

# International IR Rectifier

PD-96019A

## IRF7750PbF

HEXFET® Power MOSFET

- Ultra Low On-Resistance
- Dual P-Channel MOSFET
- Very Small SOIC Package
- Low Profile ( $< 1.1\text{mm}$ )
- Available in Tape & Reel
- Lead-Free


$V_{DSS} = -20\text{V}$

$R_{DS(on)} = 0.030\Omega$

### Description

HEXFET® power MOSFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the ruggedized device design, that International Rectifier is well known for, provides the designer with an extremely efficient and reliable device for battery and load management.

The TSSOP-8 package has 45% less footprint area than the standard SO-8. This makes the TSSOP-8 an ideal device for applications where printed circuit board space is at a premium. The low profile ( $<1.1\text{mm}$ ) allows it to fit easily into extremely thin environments such as portable electronics and PCMCIA cards.



### Absolute Maximum Ratings

	Parameter	Max.	Units
$V_{DS}$	Drain- Source Voltage	-20	V
$I_D @ T_A = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ -4.5\text{V}$	$\pm 4.7$	A
$I_D @ T_A = 70^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ -4.5\text{V}$	$\pm 3.8$	
$I_{DM}$	Pulsed Drain Current ①	$\pm 38$	
$P_D @ T_A = 25^\circ\text{C}$	Power Dissipation	1.0	W
$P_D @ T_A = 70^\circ\text{C}$	Power Dissipation	0.64	
	Linear Derating Factor	0.008	W/ $^\circ\text{C}$
$V_{GS}$	Gate-to-Source Voltage	$\pm 12$	V
$T_J, T_{STG}$	Junction and Storage Temperature Range	-55 to + 150	$^\circ\text{C}$

### Thermal Resistance

	Parameter	Max.	Units
$R_{0JA}$	Maximum Junction-to-Ambient ②	125	$^\circ\text{C/W}$

[www.irf.com](http://www.irf.com)

1

05/14/09


# IRF7750PbF

International  
Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	-20	—	—	V	$V_{\text{GS}} = 0\text{V}$ , $I_D = -250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$	Breakdown Voltage Temp. Coefficient	—	0.012	—	$\text{V}/^\circ\text{C}$	Reference to $25^\circ\text{C}$ , $I_D = -1\text{mA}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	—	0.030	$\Omega$	$V_{\text{GS}} = -4.5\text{V}$ , $I_D = -4.7\text{A}$ ②
		—	—	0.055		$V_{\text{GS}} = -2.5\text{V}$ , $I_D = -3.8\text{A}$ ②
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	-0.45	—	-1.2	V	$V_{\text{DS}} = V_{\text{GS}}$ , $I_D = -250\mu\text{A}$
$g_{\text{fs}}$	Forward Transconductance	11	—	—	S	$V_{\text{DS}} = -10\text{V}$ , $I_D = -4.7\text{A}$
$I_{\text{DSS}}$	Drain-to-Source Leakage Current	—	—	-1.0	$\mu\text{A}$	$V_{\text{DS}} = -20\text{V}$ , $V_{\text{GS}} = 0\text{V}$
		—	—	-25		$V_{\text{DS}} = -16\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $T_J = 70^\circ\text{C}$
$I_{\text{GSS}}$	Gate-to-Source Forward Leakage	—	—	-100	nA	$V_{\text{GS}} = -12\text{V}$
	Gate-to-Source Reverse Leakage	—	—	100		$V_{\text{GS}} = 12\text{V}$
$Q_g$	Total Gate Charge	—	26	39	nC	$I_D = -4.7\text{A}$
$Q_{\text{gs}}$	Gate-to-Source Charge	—	3.9	5.8		$V_{\text{DS}} = -16\text{V}$
$Q_{\text{gd}}$	Gate-to-Drain ("Miller") Charge	—	8.0	12		$V_{\text{GS}} = -5.0\text{V}$ ②
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	15	—	ns	$V_{\text{DD}} = -10\text{V}$
$t_r$	Rise Time	—	54	—		$I_D = -1.0\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	180	—		$R_D = 10\Omega$
$t_f$	Fall Time	—	210	—		$R_G = 24\Omega$ ②
$C_{\text{iss}}$	Input Capacitance	—	1700	—	pF	$V_{\text{GS}} = 0\text{V}$
$C_{\text{oss}}$	Output Capacitance	—	380	—		$V_{\text{DS}} = -15\text{V}$
$C_{\text{rss}}$	Reverse Transfer Capacitance	—	270	—		$f = 1.0\text{MHz}$

## Source-Drain Ratings and Characteristics


	Parameter	Min.	Typ.	Max.	Units	Conditions
$I_S$	Continuous Source Current (Body Diode)	—	—	-1.0	A	MOSFET symbol showing the integral reverse p-n junction diode.
$I_{\text{SM}}$	Pulsed Source Current (Body Diode) ①	—	—	-38		
$V_{\text{SD}}$	Diode Forward Voltage	—	—	-1.2		$T_J = 25^\circ\text{C}$ , $I_S = -1.0\text{A}$ , $V_{\text{GS}} = 0\text{V}$ ②
$t_{\text{rr}}$	Reverse Recovery Time	—	26	39	ns	$T_J = 25^\circ\text{C}$ , $I_F = -1.0\text{A}$
$Q_{\text{rr}}$	Reverse Recovery Charge	—	16	24	nC	$di/dt = 100\text{A}/\mu\text{s}$ ②

### Notes:


① Repetitive rating; pulse width limited by max. junction temperature.

③ When mounted on 1 inch square copper board,  $t < 10$  sec


② Pulse width  $\leq 300\mu\text{s}$ ; duty cycle  $\leq 2\%$ .




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Typical Source-Drain Diode Forward Voltage

# IRF7750PbF


International  
Rectifier




**Fig 5.** Typical Capacitance Vs.  
Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs.  
Gate-to-Source Voltage




**Fig 7.** Threshold Voltage Vs. Temperature




**Fig 8.** Maximum Safe Operating Area



**Fig 9.** Maximum Drain Current Vs.  
 Case Temperature




**Fig 10.** Typical Power Vs. Time




**Fig 11.** Typical Effective Transient Thermal Impedance, Junction-to-Ambient

# IRF7750PbF


International  
Rectifier



**Fig 12.** Normalized On-Resistance Vs. Temperature




**Fig 13.** Typical On-Resistance Vs. Drain Current




**Fig 14.** Typical On-Resistance Vs. Gate Voltage

## TSSOP8 Package Outline

Dimensions are shown in millimeters (inches)



SYMBOL	MO-153AA DIMENSIONS					
	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	---	---	1.20	---	---	.0472
A1	0.05	---	0.15	.0020	---	.0059
A2	0.80	1.00	1.05	.032	.039	.041
b	0.19	---	0.30	.0075	---	.0118
c	0.09	---	0.20	.0036	---	.0078
D	2.90	3.00	3.10	.115	.118	.122
E	6.40 BSC			.251 BSC		
E1	4.30	4.40	4.50	.170	.173	.177
e	0.65 BSC			.0256		
L	0.45	0.60	0.75	.0178	.0236	.0290
L1	0.25 BSC			.010 BSC		
$\theta$	0°	---	8°	0°	---	8°
aaa	0.10			.0039		
bbb	0.10			.0039		
ccc	0.05			.0019		
ddd	0.20			.0078		



### LEAD ASSIGNMENTS



### NOTES

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
2. DIMENSIONS ARE SHOWN IN MILLIMETERS AND INCHES.
3. CONTROLLING DIMENSION: MILLIMETER.
4. DATUM PLANE H IS LOCATED AS SHOWN.
5. DATUM A AND B TO BE DETERMINED AT DATUM PLANE H.
6. DIMENSIONS D AND E1 ARE MEASURED AT DATUM PLANE H.
7. DIMENSION L IS THE LEAD LENGTH FOR SOLDERING TO A SUBSTRATE.
8. OUTLINE CONFORMS TO JEDEC OUTLINE MO-153AA.


Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>  
[www.irf.com](http://www.irf.com)

# IRF7750PbF


International  
**IR** Rectifier

## TSSOP8 Part Marking Information

EXAMPLE: THIS IS AN IRF8852PBF



## TSSOP-8 Tape and Reel Information



NOTES:

1. TAPE & REEL OUTLINE CONFORMS TO EIA-481 & EIA-541.

Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 05/2009