Fox Part Number: 617-24.572675-1 LEAD-FREE, CERAMIC, SMD, CRYSTAL



MODEL: C1BS (Formerly FX216B Series)

RoHS / REACH Compliant / Pb-Free

| A. Specifications | | | |
|---|---------------------------------|--|--|
| Parameters | | | |
| Frequency | 24.572675 MHz | | |
| Resonance Mode | Fundamental | | |
| Frequency Tolerance @ 25°C | ±15 PPM Max | | |
| Frequency Stability, ref @ 25°C Over Operating Temp. Range | ±20 PPM Max | | |
| Temperature Range Operating (T _{OPR}) Storage (T _{STG}) | -10°C ~ +55°C -55°C ~ +125°C | | |
| Equivalent Series Resistance (ESR) | 130 Ohms Max | | |
| Shunt Capacitance (C ₀) *(1)* | 0.445 pF ±20% | | |
| Series Capacitance (C1) | 1.2 fF ±20% | | |
| Load Capacitance (CL) | 10 pF | | |
| Drive Level | 50 µW Max | | |
| Aging per year | ±2 PPM Max | | |
| Maximum Soldering Temp / Time | 260°C / 10 Seconds | | |
| Moisture Sensitivity Level (MSL) | 1 | | |
| Termination Finish: | Au over Ni | | |
| Weight (TYP) | 8.85 mg | | |

(1) Including measurement fixture



Recommended **Solder Pad Layout**



*For proper operation, pin 4 must be connected to GND.

NOTE: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

| Reference / Comments | Title / Description: | | |
|----------------------|---|----------|------------------|
| Initial release | Drawing Number: DWG-101221 Rev: A Size: A | | |
| | Part Number: 617-24.572675-1 Cage: 61429 | | Cage: 61429 |
| | Draftsperson: AR Appr | oved: CR | Date: 03-07-2018 |
| | Pag | e 1 of 2 | |

Fox Part Number: 617-24.572675-1

LEAD-FREE, CERAMIC, SMD, CRYSTAL MODEL: C1BS (Formerly FX216B Series)



┥╻┝╸

Tape & Reel Specification

| Tape Specifications (millimeters) | | | | | | |
|-----------------------------------|-----|-----|-----|-----|------|--------------|
| Α | В | С | D | E | F | STD Reel QTY |
| Φ1.55 | 4.0 | 4.0 | 3.5 | 8.0 | 0.65 | 2,000 |



| Reel Specifications (millimeters) | | | | | | |
|-----------------------------------|-----|-----|-----|------|-----|-----|
| G | Н | I | J | К | L | М |
| 2.0 | Ф13 | Φ21 | Ф60 | Ф180 | 9.0 | 2.0 |

<u>NOTE</u>: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

| Reference / Comments | Title / Description: | | |
|----------------------|---|------------------|--|
| Initial release | Drawing Number: DWG-101221 Rev: A Size: A | | |
| | Part Number: 617-24.572675-1 Cage: 61429 | | |
| | Draftsperson: AR Approved: CR | Date: 03-07-2018 | |
| | Page 2 of 2 | | |